

Products

Search :

Select Select Select Select

【1U Single】P1U-6150P



Output Wattage...

150W

Best Solution for...

Server ,Workstation ,Storage
System ,IPC

Inquiry

Dimension...

190x100x40(mm)

7.48x3.94x1.57(inch)

Input Spec...

VOLTAGE: 90 ~ 264 VAC FULL RANGE

FREQUENCY: 47 ~ 63 HZ

INPUT CURRENT: 4.0 A (RMS) FOR 110VAC

2.0 A (RMS) FOR 220VAC

INRUSH CURRENT: 65 A MAX. FOR 110 VAC

130 A MAX. FOR 220 VAC

DC Output Spec...

Output Voltage	Output Current Min.	Output Current Max.	Regulation Load	Regulation Line	Output Ripple & Noise Max. [P-P]
5V	2	14	± 5%	± 1%	70mV
12V	1	6	± 5%	± 1%	120mV
-5V	0.1	0.5	± 5%	± 1%	100mV
-12V	0.1	0.8	-10%~+10%	± 1%	120mV
3.3V	1	10	± 5%	± 1%	70mV
+5VSB	0.1	1.5	± 5%	± 1%	70mV

Features...

*Active PFC (full range), MEET IEC-1000-3-2 CLASS D

*12V Max. Current : 9A

*TEMPERATURE RANGE: OPERATING 0°C ~ 40°C.

*HUMIDITY:OPERATING:20%-95%, NON-OPERATING:10%-95%

*REMARKS:85% IS NORMAL CONDITION AND 95% IS WITH SPECIAL COATING PROCESS

*EMI NOISE FILTER: FCC CLASS B, CISPR22 CLASS B

*OVER POWER PROTECTOIN

*OVER VOLTAGE PROTECTOIN

*SHORT CIRCUIT PROTECTION

*SAFETY: UL, CSA, TUV, CCC, GOST

*Remote on/off control

*Cooling: ONE 40 mm NMB ball bearing DC Fan

*3.3V/5V Remote sensing

*Serial ATA optional

*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS.

Download

DRAWING

CB

CCC

FCC

TUV

MTBF

MTBF

CE

CE(Radiation)



Keywords Search :

New Product

1U Redundant

1U Single

2U Redundant

2U Single

3U Single

Cloud Power

Easy Swap

Medical

Micro Redundant

Mini 1U Single

Mini Redundant

N+1 Redundant

Open Frame

PS2

PS2*2 Redundant

PS2+

Redundant module