



Products

Search :


【PS2+】PSM-5660V



Output Wattage...

660W

Best Solution for...

Server ,Workstation ,Storage
System


Dimension...

160x150x86(mm)
6.3x5.91x3.39(inch)

Input Spec...

VOLTAGE: 90 ~ 264 VAC FULL RANGE
FREQUENCY : 47 ~ 63 HZ
INPUT CURRENT: 10 A (RMS) FOR 115VAC /
5 A (RMS) FOR 230VAC
INRUSH CURRENT: 20A MAX. FOR 115 VAC /
40A MAX. FOR 230 VAC
PFC CAN REACH THE TARGET OF 95% @230V, FULL LOAD

DC Output Spec...

Output Voltage	Output Current Min.	Output Current Max.	Regulation Load	Regulation Line	Output Ripple & Noise Max.[P-P]
+5V	0.5	25	±5%	±1%	50mV
+12V	1	50	±5%	±1%	120mV
-12V	0	0.8	±5%	±1%	120mV
+3.3V	0.5	25	±5%	±1%	50mV
+5VSB	0.1	3.5	±5%	±1%	50mV

Features...

- * TEMPERATURE RANGE: OPERATING 0°C ~ 50°C
- * HOLD UP TIME: WHEN POWER SHUTDOWN DC OUTPUT 5V MUST BE MAINTAIN 16MSEC IN REGULATION LIMIT AT NORMAL INPUT VOLTAGE
- * HUMIDITY: OPERATING:20%-80%, NON-OPERATING:10%-90%
- * EFFICIENCY: TYPICAL 80-85% AT 25°C 115V FULL LOAD
- * OVER POWER PROTECTOIN: 110%~150%
- * OVER VOLTAGE PROTECTION: +3.3V→3.6~4.3V, +5V→5.8~6.7V, +12V→13.2~15V
- * OVER CURRENT PROTECTION: +3.3V→29.7~40.2A, +5V→29.7~40.2A, +12V→55~68A
- * SHORT CIRCUIT PROTECTION: +5V, +3.3V, +12V, -12V
- * SAFETY: TO MEET UL, CUL, TUV, CCC
- * COOLING: ONE 60 mm DC FAN

Keywords Search:

- ▶ [New Product](#)
- ▶ [1U Redundant](#)
- ▶ [1U Single](#)
- ▶ [2U Redundant](#)
- ▶ [2U Single](#)
- ▶ [3U Single](#)
- ▶ [Cloud Power](#)
- ▶ [Easy Swap](#)
- ▶ [Medical](#)
- ▶ [Micro Redundant](#)
- ▶ [Mini 1U Single](#)
- ▶ [Mini Redundant](#)
- ▶ [N+1 Redundant](#)
- ▶ [Open Frame](#)
- ▶ [PS2](#)
- ▶ [PS2*2 Redundant](#)
- ▶ [PS2+](#)
- ▶ [Redundant module](#)

Inquiry

Download

- [CB](#)
- [TUV](#)
- [Manual-English](#)
- [Manual-Chinese](#)
- [DRAWING](#)
- [MTBF\(ROHS\)](#)
- [CCC](#)
- [FCC](#)
- [CE Radiation](#)

*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS.