



Products

Search:

Select Select Select Select

[2U Redundant] R2Z-6400P



Output Wattage...

400W

Best Solution for...

Server ,Workstation ,Storage
System ,IPC ,Communication
,Networking

Inquiry

Keywords Search :

GO!

- New Product
- 1U Redundant
- 1U Single
- 2U Redundant
- 2U Single
- 3U Single
- Cloud Power
- Easy Swap
- Medical
- Micro Redundant
- Mini 1U Single
- Mini Redundant
- N+1 Redundant
- Open Frame
- PS2
- PS2*2 Redundant
- PS2+
- Redundant module

Dimension...

265x101x84(mm)
10.43x3.98x3.31(inch)

Input Spec...

90 ~ 264 VAC FULL RANGE

DC Output Spec...

Output Voltage	Output Current Mn.	Output Current Max.	Regulation Load	Regulation Line	Output Ripple & Noise Max.[P-P]
5V	3	25	± 5%	± 1%	50mV
12V	2	28	± 7%	± 1%	100mV
-5V	0.1	0.5	± 10%	± 1%	150mV
-12V	0.1	0.8	± 10%	± 1%	150mV
3.3V	1	20	± 5%	± 1%	50mV
+5VSB	0.1	2	± 5%	± 1%	50mV

REMARKS:

- 1.TOTAL POWER OF +5V AND + 3.3V NOT EXCEED 175W
- 2.TOTAL +5V AND 3.3V AND 12V POWER NOT EXCEED 384 W

Features...

- *TEMPERATURE RANGE : OPERATING 0... --- 40..., STORAGE -20... --- 70...
- * HUMIDITY:OPERATING:20%-95%, NON-OPERATING:10%-95%
- * REMARKS:85% IS NORMAL CONDITION AND 95% IS WITH SPECIAL COATING PROCESS
- *EMI NOISE FILTER: FCC CLASS B, CISPR22 CLASS B
- *SAFETY: MEET UL 1950, CSA 22.2 NO/ 950, TÜV IEC 950
- *REMOTE ON / OFF CONTROL
- *FAULTY ALARM METHODS : LED, BUZZER, TTL SIGNAL
- *HOT-SWAPPABLE / HOT-PLUGGABLE 1 + 1 REDUNDANCY FUNCTION
- *BALANCE LOAD SHARING DESIGN
- *ISOLATION: BUILT-IN IN THE POWER MODULE
- *MEET IEC-1000-3-2 CLASS D (ACTIVE PFC)
- *COOLING : TWO 38 mm DC FANS IN EACH MODULE

*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS.

DownLoad

- Drawing
- CB
- TUV
- FCC
- CCC
- MTBF
- MANUAL
- MTBF(ROHS)
- MTBF(ROHS)(W/O FAN)
- MTBF(ROHS)(40...)
- MTBF(ROHS)(55...)
- CE